

BACKFIX

Bracket with one way friction for screwing / unscrewing watchbacks...

The new friction wheel developed by VOH makes this bracket an essential tool with any workshop in after-sales service or production. The simple and reliable release system ensures sufficient and regular locking on watertight watchcases.



Art. VOH 26.00387

Factory pre-setted torques :

Repeatability:

Range of setting:

Ø wheel:

Distance base-stitch:

Distance axis- vertical frame:

Adjustment bases:

2.5 Nm

± 10%

1.2 – 3.5 Nm

160 mm

80 mm

44 mm

Slit 12.0 x 5.5
mm / hole Ø 12.0
mm

Key adjustment (Rawlyer):

Slit 10.0 x 3.5
mm / hole Ø 9.0
mm

Key fixation (Rawlyer):

Key adjustment (Bergeon):

Tie rod M5
Slit 8.5 mm / hole
Ø 8.0 x 9.0 mm
with side screw
M4

Key fixation (Bergeon):

Delivery: With base board in black agglomerate wood 275 x 160 mm

Note: The modification of the friction torque requires the use of adequate tools

Adjustable wrench VOH with 3 dogs and interchangeable bits for funds multi-sides, with 6 notches NIHS or round notches.

For bracket with Bergeon adjustment: **Art. 26.00360**

For bracket with Rawlyer adjustment: **Art. 26.00090**



Universal base maintaining the watchcases between the horns and adaptable on any bracket with a Rawlyer adjustment.

Art. VOH 26.00880



ÉQUIPEMENT HORLOGER

VOH SA

CP66 Z.I. La Praye 5a
T +41(0)32 945 17 45

CH-2608 Courtelary
F +41(0)32 945 17 55

info@voh.ch
www.voh.ch